

# SFP-1000Base-BX34

## 1.25 Gb/s bi-directional 1310/1490 SFP transceiver family

### DESCRIPTION

The SFP-1000Base-BX34 transceivers are fully compliant with the latest industrial SFP Multi-Source Agreement (MSA) and IEEE 802.3ah for Gigabit Ethernet 1000Base-BX. They support data rate at 1.25 Gbps and are suitable for Gigabit Ethernet applications. The transceivers operate bi-directionally on single fiber at wavelengths of 1310 nm and 1490 nm. The modules are hot pluggable and come in three variants for 10 km and 40 km transmission on SM fiber.

### APPLICATIONS

- Gigabit Ethernet
- FTTx

### FEATURES

- Up to 40 km transmission on SM fiber
- 1310nm/1490nm operation
- Compliant to SFP MSA and SFF-8472
- Serial ID functionality
- Digital Diagnostics Monitoring
- Hot-Pluggable SFP footprint
- Simplex LC interface for bi-directional operation
- Operating temperature 0°C to 70°C



### OPTICAL PARAMETERS

Part no.	SM/MM Fiber	Wavelength [nm] TX/RX	Opt. Output Power [dBm]	Opt. Receiver Sensitivity [dBm]	Power Budget [dB]
SFP-1000B-BX10D-34	SM	1310/1490	-10 to -5	-23 to -3	13
SFP-1000B-BX10D-43	SM	1490/1310	-10 to -5	-23 to -3	13
SFP-1000B-BX40D-34	SM	1310/1490	-5 to 0	-23 to -3	18
SFP-1000B-BX40D-43	SM	1490/1310	-5 to 0	-23 to -3	18

### ORDERING INFORMATION

Part no.	Description
SFP-1000B-BX10D-34	SFP BiDi, 1.25Gbps GigE, DDM, SM, TX1310/RX1490, 10km, 13dB
SFP-1000B-BX10D-43	SFP BiDi, 1.25Gbps GigE, DDM, SM, TX1490/RX1310, 10km, 13dB
SFP-1000B-BX40D-34	SFP BiDi, 1.25Gbps GigE, DDM, SM, TX1310/RX1490, 40km, 18dB
SFP-1000B-BX40D-43	SFP BiDi, 1.25Gbps GigE, DDM, SM, TX1490/RX1310, 40km, 18dB