

SFP-10Gbase-T

10GBase-T SFP transceiver for Ethernet switches

DESCRIPTION

The SFP-10GBase-T electrical SFP transceiver (RJ45) is designed for high speed Gigabit Ethernet data links up to 10 Gb/s, with XGMII interface. It is a high performance integrated duplex data link for bi-directional communication over CAT 6a/7 unshielded twisted pair copper cable. It is compliant with the MSA Small Form Factor Pluggable (SFP) specification. The transceiver is hot pluggable and operates at +3.3V.

The RJ45 connector supports shielded and unshielded cables. The connector is mechanically robust enough and designed to prevent loss of link, when the cable is positioned or moves in different angles. The connector passes the “wiggle” RJ45 connector operational stress test.

APPLICATIONS

- 10GBase-T

FEATURES

- XGMII interface
- Compatible with Small-Form Pluggable (SFP) MSA
- Up to 30 m on CAT 6a/7 UTP cables
- RJ45 connector type
- Compatible with FCC 47 CFR Part, Class B Electromagnetic Interference (EMI)
- Compatible with IEC 61000-4-2 and GR-1089-CORE Electrostatic Discharge (ESD)
- +3.3V single power supply
- Case operating temperature range:-5°C to 85°C



FIBERWORKS

ORDERING INFORMATION

Part no.	Description
SFP-10Gbase-T	SFP, 10Gbase-T Copper Interface, RJ45, 30m on Cat6/7